

Pressure Sustaining and Reducing Valve

- Protecting lower pressure zones
- Prioritizing higher pressure zones
- Preventing pipeline emptying
- Ensuring controlled pipeline fill-up
- Pump overload & cavitation protection
- Compensating during groundwater drawdown

The Model 723 Pressure Sustaining and Reducing Valve is a hydraulically operated, diaphragm actuated control valve with two independent functions. It sustains minimum pre-set upstream pressure regardless of fluctuating flow or varying downstream pressure, and it prevents downstream pressure from rising above maximum pre-set regardless of fluctuating flow or excessive upstream pressure.




Features and Benefits

- **Line pressure driven** – Independent operation
- **In-line serviceable** – Easy maintenance
- **Double chamber design**
 - Moderated valve reaction
 - Protected diaphragm
- **Flexible design** – Easy addition of features
- **Variety of accessories** – Perfect mission matching
- **"Y" or angle, wide body** – Minimized pressure loss
- **Semi-straight flow** – Non-turbulent flow
- **Stainless Steel raised seat** – Cavitation damage resistant
- **Obstacle free, full bore** – Uncompromising reliability
- **V-Port Throttling Plug** – Low flow stability

Major Additional Features

- Solenoid control – **723-55**
- Check feature – **723-20**
- High sensitivity pilots – **723-12**
- Solenoid control & check feature – **723-25**
- Downstream over pressure guard – **723-48**
- Proportional – **723-PD**

See relevant BERMAD publications.



Operation

The Model 723 is a pilot controlled valve equipped with two adjustable, 2-Way pilots, pressure sustaining (PS) and pressure reducing (PR), operating independently in series.

The needle valve [1] continuously allows flow from the valve inlet into the upper control-chamber [2].


The PS pilot [3] and the PR pilot [4] together control outflow from the upper control chamber.

Should upstream pressure fall below PS pilot setting, the pilot closes causing pressure to accumulate in the upper control chamber. The main valve throttles closed sustaining upstream pressure at the pilot setting.

Should upstream pressure rise above PS pilot setting, the pilot releases accumulated pressure from the upper control chamber to the main valve outlet through the held open PR pilot, opening the main valve.

Should opening the main valve cause downstream pressure to rise above PR pilot setting, the pilot closes, causing the main valve to throttle closed reducing downstream pressure to PR pilot setting.

The needle valve controls the closing speed. The downstream cock valve [5] enables manual closing.



Note: For 16" and larger valves, see "Pilot Valve Selection" table at the last page.

Engineer Specifications


The Pressure Sustaining and Reducing Valve shall sustain minimum pre-set upstream pressure regardless of fluctuating flow or varying downstream pressure, and shall also prevent downstream pressure from rising above maximum pre-set regardless of fluctuating flow or excessive upstream pressure.

Main Valve: The main valve shall be a center guided, diaphragm actuated globe valve of either oblique (Y) or angle pattern design. The body shall have a replaceable, raised, stainless steel seat ring. The valve shall have an unobstructed flow path, with no stem guides, bearings, or supporting ribs. The body and cover shall be ductile iron. All external bolts, nuts, and studs shall be Duplex® coated. All valve components shall be accessible and serviceable without removing the valve from the pipeline.

Actuator: The actuator assembly shall be double chambered with an inherent separating partition between the lower surface of the diaphragm and the main valve. The entire actuator assembly (seal disk to top cover) shall be removable from the valve as an integral unit. The stainless steel valve shaft shall be center guided by a bearing in the separating partition. The replaceable radial seal disk shall include a resilient seal and shall be capable of accepting a V-Port Throttling Plug by bolting.


Control System: The control system shall consist of two 2-way adjustable, direct acting pilots (pressure sustaining and pressure reducing), a needle valve, isolating cock valves, and a filter. All fittings shall be forged brass or stainless steel. The assembled valve shall be hydraulically tested and factory adjusted to customer requirements.

Quality Assurance: The valve manufacturer shall be certified according to the ISO 9001 Quality Assurance Standard. The main valve shall be certified as a complete drinking water valve according to NSF, WRAS, and other recognized standards.



Typical Applications

Water is pumped from a deep well to the reservoir through a line also supplying nearby consumers along the way. Water is then supplied from the reservoir to both higher and lower elevation consumers. Both parts of the system require pressure sustaining and reducing solutions.




Groundwater Draw Down System

In deep well pumping systems, the groundwater level varies according to: seasonal changes, seepage rate, and demand. These systems require a solution to a unique combination of issues:

- Consumer demand or filling an empty line results in pump overload and cavitation, requiring pressure sustaining.
- Deep well pumps boost a constant ΔP , resulting in high ground level raising the discharge pressure, requiring pressure reducing.

The Model 723 provides a complete solution for both of these issues. Adding check feature "20", saves the cost of a line-sized check valve.





Gravity Fed Supply Line

Where consumers at both higher and lower elevations use the same distribution network:

- Consumers located at higher elevation need protection against over demand by the lower zone.
- Lower zone consumers need protection against high gravity fed pressure.

The Model 723, being both a pressure sustaining and reducing valve, simultaneously fulfills both requirements.






Technical Data


Dimensions and Weights

Size		A, B		C		L		H		Weight	
mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	kg	lbs
40	1 1/2"	350	14	180	7	205	8.1	239	9.4	9.1	20
50	2"	350	14	180	7	210	8.3	244	9.6	10.6	23
65	2 1/2"	350	14	180	7	222	8.7	257	10.1	13	29
80	3"	370	15	230	9	250	9.8	305	12.0	22	49
100	4"	395	16	275	11	320	12.6	366	14.4	37	82
150	6"	430	17	385	15	415	16.3	492	19.4	75	165
200	8"	475	19	460	18	500	19.7	584	23.0	125	276
250	10"	520	21	580	23	605	23.8	724	28.5	217	478
300	12"	545	22	685	27	725	28.5	840	33.1	370	816
350	14"	545	22	685	27	733	28.9	866	34.1	381	840
400	16"	645	26	965	38	990	39.0	1108	43.6	846	1865
450	18"	645	26	965	38	1000	39.4	1127	44.4	945	2083
500	20"	645	26	965	38	1100	43.3	1167	45.9	962	2121



Data is for Y-pattern, flanged, PN16 valves
 Weight is for PN16 basic valves
 "C" enables removing the actuator in one unit
 "L", ISO standard lengths available
 For more dimensions and weights tables, refer to Engineering Section

Flow Chart



Data is for Y-pattern, flat disk valves
 For more flow charts, refer to Engineering Section

Main Valve

- Valve Patterns:** "Y" (globe) & angle
- Size Range:** 1 1/2"-32" (40-800 mm)
- End Connections (Pressure Ratings):** Flanged: ISO PN16, PN25 (ANSI Class 150, 300)
- Threaded:** BSP or NPT
- Others:** Available on request
- Working Temperature:** Water up to 80°C (180°F)
- Standard Materials:** Body & Actuator: Ductile Iron
- Internals:** Stainless Steel, Bronze & coated Steel
- Diaphragm:** NBR Nylon fabric-reinforced
- Seals:** NBR
- Coating:** Fusion Bonded Epoxy, RAL 5005 (Blue) NSF & WRAS approved or Electrostatic Polyester Powder, RAL 6017 (Green)

Control System

- Standard Materials:** Accessories: Bronze, Brass, Stainless Steel & NBR
- Tubing:** Copper or Stainless Steel
- Fittings:** Forged Brass or Stainless Steel
- Pilot Standard Materials:** Body: Brass, Bronze or Stainless Steel
- Elastomers:** NBR
- Springs:** Galvanized Steel or Stainless Steel
- Internals:** Stainless Steel

Pilot Valve Selection

Valve Size	Pilot Setting (bar)	Pilot Type		
		#2PB #3PB	#2 #3	#2HC #3HC
1 1/2-4"	<15	■		
40-100 mm	>15		●	
6-14"	<15	■		
150-350 mm	>15		●	
16-32"	<15			■
400-800 mm	>15			●

■ Standard model ● with high pressure setting kit

How to Order

Please specify the requested valve in the following sequence: (for more options, refer to Ordering Guide)

Sector	Size	Primary Feature	Additional Feature	Pattern	Body Material	End Connections	Coating	Voltage & Position	Tubing & Fittings	Additional Attributes
WW	6"	723	00	Y	C	16	EB	-	CB	VI
Waterworks	1 1/2 - 32"	Pressure Sustaining and Reducing	No Additional Feature	Oblique (up to 20") Angle (up to 18") Globe (24-32" only)	Ductile Iron Standard Cast Steel St. Steel 316 Nickel Alumin. Bronze	Epoxy FB Blue Polyester Green Polyester Blue Uncoated	EB PG PB UC		Copper Tubing & Brass Fittings Plastic Tubing & Brass Fittings St. St. 316 Tubing & Fittings	CB PB NN
			Closing and Opening Speed Control						Valve Position Indicator	I
			Automatic Regulation Override						Large Control Filter	F
			High sensitivity pilot						V-Port Throttling Plug	V
			Check Valve						Electric Limit Switch	S
			Solenoid Controlled & Check Valve						3-Way Control Loop	X
			Multi-Setting Levels - Electrically Selected						Valve Position Transmitter	Q
			Downstream Over Pressure Guard						St. St. 316 Control Accessories	N
			Hydraulic Control						St. St. 316 Internal Trim (Closure & Seat)	T
			Solenoid Controlled						St. St. 316 Actuator Internal Assembly	D
			Electric Override						Delrin Bearing	R
									Viton Elastomers for Seals & Diaphragm	E
									Pressure Gauge	6

Multiple choices permitted

Use when additional electric control feature is selected

Multiple choices permitted

